



Thermoflex™

Warm Edge Spacer

SAVE energy with Lowest Conductivity Spacers - **0.135W/mK**

SAVE energy with lowest Psi values

SAVE energy with reduced overall window U-values

SAVE costs on the best futureproof window components

	Plastic window frame	Wood window frame
Double Glazing	0.030	0.029
Triple Glazing	0.029	0.027

www.thermoflexwarmedge.com



Sizes made to exacting standards with minimal tolerance

Passive House: www.passivehouse.com

Bundesverband Flachglas Data: www.bundesverband-flachglas.de



THERMOSEAL GROUP
Dedicated to Insulated Glass





Thermoflex

Warm Edge Spacer

Thermoflex Sizes and Reel Information*

Width \pm 3% (mm)	Metres / Reel	Metres / Auto Reel	Width \pm 0.0078 (inches)	Feet / Reel	Feet / Auto Reel
4.8 (3/16")	609	1827	0.189	1998	5994
6.0 (1/4")	460	1,380	0.236	1509	4528
8.0 (5/16")	335	1,005	0.315	1099	3297
10.0 (3/8")	305	915	0.394	1000	3002
11.1 (7/16")	273	819	0.437	895	2685
12.0	245	735	0.472	803	2411
12.7 (1/2")	243	729	0.5	797	2391
14.0 (9/16")	215	645	0.551	705	2116
16.0 (5/8")	205	615	0.630	672	2017
18.0 (11/16")	185	555	0.709	606	1821
19.1 (3/4")	175	525	0.752	574	1722
20.0	155	465	0.787	508	1525

*Other widths available on request. Smaller reel lengths are also available: 6-10mm widths are available in 40m (131.2ft) lengths, and 12-20mm widths are available in 20m reels (65.6ft).

Standard Spacer height is 4.8mm \pm 0.3mm (0.189 \pm 0.0118 Inch). Sizes larger than 8mm (0.315 Inch) have \pm 3% tolerance on width and sizes 8mm and smaller have a \pm 0.26mm (0.0102 Inch) tolerance on width.

Please note:

- Data is correct at time of print but is subject to change as further tests are carried out.
- Test figures required within different countries and zones may vary. Select the data from the values above. If further values are required for Thermoflex, please don't hesitate to contact Thermoseal Group.



Download QR Code reader on your mobile phone to scan image above for online location of data sheets and downloads

These details are based on our current knowledge. Therefore, it is not intended to assure legally binding or to guarantee the nature of the products, the trade capability of the products and the suitability for a certain use. We reserve the right to make technical alterations.

